




## NUMINOS® MOVE DL XL

Indoor LED recessed ceiling light white/white 4000K  
20° rotating and pivoting

The NUMINOS light system from SLV combines technology, design and functionality like no other. With different downlights and spotlights, you can experience a thousand lighting design possibilities. Also with the NUMINOS® MOVE DL XL recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. The recessed ceiling light has a power consumption of 37.4 watts, a luminous flux of 3800 lumens, a colour temperature of 4000 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



## TECHNICAL DATA

|                                     |             |
|-------------------------------------|-------------|
| Item no.:                           | 1003758     |
| Number of different light outlets   | 1           |
| Secondary power / secondary voltage | 1050mA      |
| Height                              | 11.8 cm     |
| Diameter                            | 19 cm       |
| Installation diameter               | 17.5 cm     |
| Installation depth                  | 13 cm       |
| Net weight                          | 0.66 kg     |
| Gross weight                        | 0.706 kg    |
| IP Code                             | IP 20       |
| Safety class                        | III         |
| Impact resistance class             | IK02        |
| Impact resistance                   | 0,2 Joule   |
| Assembly                            | Recessed    |
| Assembly details                    | Ceiling     |
| Wattage                             | 37.4 W      |
| Lumen                               | 3800 lm     |
| Colour temperature                  | 4000 Kelvin |
| Beam angle                          | 20 °        |
| Color                               | white       |
| CRI                                 | 90          |
| UGR ≤                               | 19          |

## Light Source

|        |   |
|--------|---|
| 791850 |  |
|--------|---|

## Accessories

|         |   |
|---------|---|
| 1004059 | LED driverm 40W multi mA                            |
| 1004066 | LED driver , 28-40W 1000mA PHASE                    |
| 1004071 | LED driver 4.2-50W 1050mA DALI                      |
| 1004798 | NUMINOS® XL , diffuser Ellipse                      |
| 1004799 | NUMINOS® XL , diffuser Prisma                       |
| 1004800 | NUMINOS® XL , diffuser Frosted                      |
| 1004801 | NUMINOS® XL , diffuser Wabe                         |
| 1006151 | Numinos® XL Mounting Frame , round 240/180mm black  |
| 1006152 | Numinos® XL Mounting Frame , round 240/180mm white  |
| 1006153 | Numinos® XL Mounting Frame , square 240/180mm black |
| 1006154 | Numinos® XL Mounting Frame , square 240/180mm white |

|                             |        |
|-----------------------------|--------|
| LXXBXX data                 | L80B50 |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C  |
| BIG WHITE Page              | 46     |