




NUMINOS® CL DALI L

Indoor LED surface ceiling light white/black 2700K 60°

The NUMINOS light system from SLV perfectly combines function, design and technology. With a variety of downlights and spotlights, you provide a thousand lighting design options. Like with the NUMINOS® CL DALI L indoor ceiling-mounted light LED, which impresses with its high-quality workmanship and light. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The recessed ceiling light convinces with a power consumption of 28 watts, luminous flux of 2475 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.



TECHNICAL DATA

| Item no.: | 1004608 |
|--|------------------------|
| Primary nominal voltage | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary volta- ge | 700mA |
| Height | 21.3 cm |
| Diameter | 10 cm |
| Net weight | 1.115 kg |
| Gross weight | 1.45 kg |
| Safety class | I |
| Assembly | Surface |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | DALI |
| Wattage | 28 W |
| Lumen | 2475 lm |
| Colour temperature | 2700 Kelvin |
| Beam angle | 60 ° |
| Color | white |
| CRI | 90 |
| UGR≤ | 22 |
| LXXBXX data | L80B50 |
| BIG WHITE Page | 84 |
| | |



Light Source

| 791800 | A E |
|-------------|-------------------------------|
| Accessories | |
| 1006169 | NUMINOS® L , white front ring |