


MILANDOS 4

black recessed ceiling light, 2700K 45°

Minimalist, innovative and compact in design, the MILANDOS recessed ceiling light creates high-quality lighting. It shines above all with a true-to-life colour reproduction index of over 90 out of 60,000. With a UGR of 16, it produces glare-free light. The simple design of the recessed ceiling light made of aluminium and polycarbonate (PC) blends seamlessly into any room. The spotlight is also quick and easy to install. Experience MILANDOS in action and convince yourself of a successful lighting experience.



TECHNICAL DATA

| | |
|-------------------------------------|-------------|
| Item no.: | 1005407 |
| Secondary power / secondary voltage | 700mA |
| Length | 13.6 cm |
| Width | 5.6 cm |
| Height | 4.3 cm |
| Installation length | 13 cm |
| Installation width | 4.9 cm |
| Installation depth | 7 cm |
| Net weight | 0.25 kg |
| Gross weight | 0.268 kg |
| IP Code | IP 20 |
| Safety class | III |
| Impact resistance class | IK02 |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Lumen | 510 lm |
| Colour temperature | 2700 Kelvin |
| Beam angle | 45 ° |
| Color | black |
| CRI | 90 |
| UGR ≤ | 16 |
| LXXBXX data | L80B50 |

Light Source

| | |
|--------|---|
| 916372 |  |
|--------|---|

Accessories

| | |
|---------|--|
| 1002423 | LED driver MEDO 300 , dimmable DALI/1-10V |
| 464142 | LED DRIVER , 10.5W, 700mA, incl. strain relief, dimmable |

| | |
|---------------------|-------|
| Ambient temperature | 30 °C |
| BIG WHITE Page | 349 |