



NUMINOS® GIMBLE XS

white recessed ceiling light, 4000K 40°

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With different downlights and spotlights, you provide a thousand lighting design possibilities. Like with the NUMINOS® GIMBLE XS recessed ceiling light, which impresses with its high-quality workmanship and light. In this way, you can create discreet, modern and space-saving lighting that draws the focus to objects or the room. This means that simple installation is a mere formality. When will you choose SLV's modular variety?



TECHNICAL DATA

| | |
|--|-------------|
| Item no.: | 1005862 |
| Number of different light outlets | 1 |
| Secondary power / secondary voltage ^e | 200mA |
| Height | 5.7 cm |
| Diameter | 8 cm |
| Installation diameter | 6.8 cm |
| Installation depth | 11 cm |
| Net weight | 0.11 kg |
| Gross weight | 0.118 kg |
| Safety class | III |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Wattage | 7 W |
| Lumen | 730 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 40 ° |
| Color | white |
| CRI | 90 |
| UGR ≤ | 22 |
| BIG WHITE Page | 49 |

Light Source

| | |
|--------|---|
| 798305 |  |
|--------|---|

Accessories

| | |
|---------|---|
| 1005609 | LED Driver , 200mA 10W PHASE, Quick Connector |
| 1005610 | LED Driver , 200mA 10-W, Quick Connector |
| 1005611 | LED Driver , 200mA 13,5W DALI dimmable, Quick Connector |
| 1005612 | NUMINOS® XS , diffuser |
| 1005613 | NUMINOS® XS , transparent diffuser |
| 1005614 | NUMINOS® XS , frosted diffuser |
| 1005615 | NUMINOS® XS , black diffuser |
| 1006135 | Numinos® XS Mounting Frame , round 160/70mm black |
| 1006136 | Numinos® XS Mounting Frame , round 160/70mm white |
| 1006137 | Numinos® XS Mounting Frame , square 160/70mm black |
| 1006138 | Numinos® XS Mounting Frame , square 160/70mm white |