




## NUMINOS® GIMBLE S

white / black recessed ceiling light, 3000K 40°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With different downlights and spotlights, you provide a thousand lighting design possibilities. This also includes NUMINOS® GIMBLE S, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



## TECHNICAL DATA

Item no.:	1005897
Number of different light outlets	1
Secondary power / secondary voltage	250mA
Height	7 cm
Diameter	10 cm
Installation diameter	9 cm
Installation depth	7 cm
Net weight	0.18 kg
Gross weight	0.193 kg
Safety class	III
Assembly	Recessed
Assembly details	Ceiling
Wattage	8.6 W
Lumen	690 lm
Colour temperature	3000 Kelvin
Beam angle	40 °
Color	white
CRI	90
UGR ≤	19
BIG WHITE Page	51

## Light Source

791815	
--------	-----------------------------------------------------------------------------------

## Accessories

1004055	LED driver , 6.5-10W 250mA PHASE
1004058	LED driver , 6.5-10W 250mA
1004067	LED driver , 15W 250mA DALI
1004786	NUMINOS® S , diffuser Ellipse
1004787	NUMINOS® S , diffuser Prisma
1004788	NUMINOS® S , diffuser Frosted
1004789	NUMINOS® S , diffuser Wabe
1006139	Numinos® S Mounting Frame , round 160/100mm black
1006140	Numinos® S Mounting Frame , round 160/100mm white
1006141	Numinos® S Mounting Frame , square 160/100mm black
1006142	Numinos® S Mounting Frame , square 160/100mm white