





## KADUX 2 SET

recessed fitting, double-headed LED, 3000K, rectangular, matt black, 38°, 15W, incl. driver

The KADUX recessed fitting series has a robust housing with appealing, high-quality looks. This LED set is multi-directional, allowing individual focus of the light beam. The KADUX 2 SET comes ready for direct connection to 230V mains and is available in matt black, matt white or brushed aluminium, as well as in single, double, or triple-headed variations.



## TECHNICAL DATA

Item no.:	115710
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	350mA
Length	15 cm
Width	9 cm
Height	8.5 cm
Installation length	14 cm
Installation width	8 cm
Installation depth	8 cm
Net weight	0.541 kg
Gross weight	0.61 kg
IP Code	IP 20
Safety class	II
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	Leading edge, trailing edge
Wattage	14 W
Lumen	1290 lm
Colour temperature	3000 Kelvin
Beam angle	38 °
Color	black

## Light Source

916451	
--------	---

<b>CRI</b>	80
<b>LXXBXX data</b>	L70B50
<b>Minimum ambient temperature</b>	-20 °C
<b>Maximum ambient temperature</b>	35 °C
<b>BIG WHITE Page</b>	379